

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)


PCT

(10) International Publication Number
WO 03/061008 A1

- (51) International Patent Classification⁷: H01L 27/00, G09G 3/32, H04N 1/028
- (21) International Application Number: PCT/IB02/05717
- (22) International Filing Date:
23 December 2002 (23.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02075200.2 17 January 2002 (17.01.2002) EP
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): HUIBERTS, Johannes, N. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SEMPEL, Adrianus [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SNIJDER, Pieter, J. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN TONGEREN, Henricus, F., J., J. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LIEDENBAUM, Coen, T., H., F [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN DE WALLE, Gerjan, F., A. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: DEGUELLE, Wilhelmus, H., G.; internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

[Continued on next page]

(54) Title: SCANNING DISPLAY



(57) Abstract: This invention relates to a display device (5) comprising first and a second sub-pixel (5a, 5b), said first sub-pixel (5a) emitting light of a first wavelength (λ_1) and said second sub-pixel (5b) emitting light of a second wavelength (λ_2), said first sub-pixel (5a) comprising a first organic electroluminescent layer (1a), such as a polymer or a small- compound molecule layer, which is sandwiched between a front and a back electrode (2a, 3a), with a first state in which an emission driving signal (V_{ai}) is applied across said first layer (1a) for generating an emission state in which light of said first wavelength (λ_1) is emitted, and with a second state in which a sensing driving signal (V_{bs}) is applied across said first layer (1a), whereby light of said second wavelength (λ_2) incident on said first sub-pixel (5a) can be detected. Preferably, said first electrodes (2a, 3a) are held at essentially the same potential.